

Novaflex®

High Temperature Duct

U-Lok 420

The combination of a standard external helix as a scuff guard and a non-glue construction results in the industry standard high-temperature duct. **Flame test UL94V-0 compliant**


Applications

- Gas exhaust control
- Hot fume control
- Hot air supply and removal

**A negative pressure fan system with ambient air inlet is recommended to maximize effectiveness and life of duct. It is important to size the duct diameter according to the exhaust output. *Not recommended for diesel applications*

Specifications

- Material: Fiberglass/Silicone - with additional silicone coating
- Construction: Mechanical bond, corrosion resistant helix
- Diameters: 3" to 24" I.D.
- Bend radius: = 1.5" x I.D.
- Weight: 6" I.D. = 1.1 lbs/ft. Length: 25 ft
- Compression Ratio: 5:1
- Colour: Metallic Grey
- Temperature range: -65°F (-54°C) to +500°F (+260°C) intermittent.



Specification Chart

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	8	6.8	3.7	3	2.3	1.4	1	.75
Negative Pressure Inch. H.g	7	4.5	2.1	1.6	1.2	.7	.45	.3
Weight per Foot	.24	.34	.4	.5	.68	.98	1.02	1.26

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete Terms and Conditions of Sale located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

01.2024

IN USA

North Carolina
449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey
1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis
7812 Moller Road
Indianapolis, IN 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario
555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral
18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk