

# Novaflex®

# Oilfield Vac/Frac Hose

## Novaflex® 3275

### Corrugated Oil field Vac/Frac Hose

This is a rugged suction and discharge, flexible hose designed for oil field vacuum truck and oil field fracturing applications. This hose is ideal where applications require a hose designed for the transfer of salt & fresh water, tank bottoms, drilling mud, combined with dilute solutions of crude oil. (Not for use with oil based fluids)

*Not recommended for use with refined petroleum products such as gasoline.* Not for use with Bio fuels.

### Specifications

Tube: Black blended nitrile

Reinforcement: Multiple tire cord layers & dual wire helix, full suction and discharge

Cover: Black abrasion, ozone & UV resistant

Temperature range: -40° to 180°F

Branding: Full suction /150 psi WP

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.



## Specification Chart

Product No	ID"	OD"	WP	MBR	Wt/Ft
3275BT-02000-00	2	2.49	150 psi	6"	1.23
3275BT-03000-00	3	3.58	150 psi	8"	2.07
3275BT-04000-00	4	4.59	150 psi	12"	2.87
3275BT-06000-00	6	6.74	150 psi	24"	5.81
3275BT-08000-00	8	8.75	150 psi	40"	8.05
3275BT-10000-00	10	10.77	100 psi	60"	11.49
3275BT-12000-00	12	12.75	40 psi	72"	12.70

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: [www.novaflex.com](http://www.novaflex.com) | [www.z-flex.com](http://www.z-flex.com) | [www.flexmaster.com](http://www.flexmaster.com).

03.2020

## IN USA

### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

### Indianapolis

7812 Moller Road  
Indianapolis, IN 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

## IN CANADA

### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686-8349  
800-563-3539

## IN U.K.

### Bromborough, Wirral

18 Candy Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
[www.novaflex.co.uk](http://www.novaflex.co.uk) Email: [sales@novaflex.co.uk](mailto:sales@novaflex.co.uk)