



NOVAFLEX[®]

PROVIDING HOSE & DUCT SOLUTIONS



ABRASION RESISTANT
Dredge Sleeve
Sand Discharge Hose

Novaflex®

Dredge Sleeve Sand Discharge

Novaflex 5331

Dredge Sleeve/Sand Discharge Hose

A specially compounded abrasive resistant and static conductive hose. Hose manufactured to very close O.D. tolerances.

Specifications

Tube: Black abrasion resistant synthetic rubber. Reinforcement: Polyester Tire cord. Cover: Black abrasion and weather resistant synthetic rubber. Length 20 feet. Temperature Range: -40°F (-40°C) to +180°F (+82°C).

Novaflex 5332

Sand Suction Hose

A specially compounded abrasive resistant and static conductive hose. Hose manufactured to very close O.D. tolerances.

Specifications

Tube: Black abrasion resistant synthetic static conductive rubber. Reinforcement: Polyester tire cord with helix wire. Cover: Black abrasion and weather resistant synthetic rubber. Length 20 feet. Temperature Range: -40°F (-40°C) to +180°F (+82°C).

Novaflex 5332YG = Yellow Novaware tube - superior abrasion resistance. Temperature to 160°F (171°C)



Part No.	I.D. (in)	O.D. (in)	Tube Gauge	Plies	WP psi	WT LBS/FT
5331BS-04500-00	4½	5.73	¾	4	150	5.45
5331BS-06000-00	6	7.25	¾	4	150	7.51
5331BS-06625-00	6¾	8.07	¾	6	150	9.26
5331BS-08625-00	8¾	10.19	¾	8	150	12.97
5331BS-10750-00	10¾	12.50	½	8	150	17.83
5331BS-12775-00	12¾	14.55	½	8	150	22.80
5331BS-14000-00	14	16.04	½	12	150	27.21
5331BS-16000-00	16	18.04	½	12	150	30.82

Part No.	I.D. (in)	O.D. (in)	Tube Gauge	Plies	WP psi	WT LBS/FT
5332BS-04000-00	4	5.54	¾	4	150	6.75
5332BS-04500-00	4½	5.95	¾	4	150	7.46
5332BS-06000-00	6	7.57	¾	4	100	11.37
5332BS-06625-00	6¾	8.20	¾	4	100	12.41
5332BS-08000-00	8	9.64	¾	6	100	15.86
5332BS-08625-00	8¾	10.32	¾	6	100	16.87
5332BS-10000-00	10	12.06	½	6	100	25.42
5332BS-10750-00	10¾	12.86	½	6	100	22.06
5332BS-12000-00	12	14.11	½	6	100	30.55
5332BS-12750-00	12¾	14.86	½	6	100	32.29
5332BS-14000-00	14	16.37	½	8	100	42.66

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

04.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IN 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk